

Daffodil International University

Faculty of Science & Information Technology Department of Computer Science and Engineering

Final Term Examination, Spring-2024

Course Code: CSE113 Course Title: Programming and Problem-Solving Batch: 66

Level: 1 Term: 1

Exam Duration: 2.0 Hours

Marks: 40

Answer ALL Questions

[The figures in the right margin indicate the full marks and corresponding course outcomes. All portions of each question must be answered sequentially.]

ı) #includ <stdio.h></stdio.h>		[3	1 2
tract myStructure {		13	'
Int myNum;			
<u>Char</u> myLetter;			
,		- 1	
nt main() {			
struct myStructure s1;		-	
s1.myNum = 13;			
sf.myLetter = 'B';			
printf("My number: &d\n", s1.myNum);			
printf("My letter: &c\n", s1.myLetter);			1
retarn 0;			
}	,		
		[3]	
Rewrite the code without any errors.		[3]	
enerate the output for the given codes be	low (write only the output segment in a box):		
S			CO
		3+	CO 3
a)	b)	3+	1
	b) . #include <stdio.h></stdio.h>	3+3	1
a) finclude <stdio.h> nt main() {</stdio.h>	b) #include <stdio.h> void pattern(int r) {</stdio.h>	11	1
a) tinclude <stdio.h></stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j;</stdio.h>	11	1
a) finclude <stdio.h> nt main() {</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) {</stdio.h>	11	1
finclude <stdio.h> nt main() { int a = 5, b = 10;</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1, j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) {</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int,*x,*y;</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) {</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b;</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d ", n++); }</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1, j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) {</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b;</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d ", n++); }</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int.*x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d ", n++); }</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d ", n++); }</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d ", n++); } printf("\n"); } }</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d", n++); } printf("\n"); } } int main() {</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d", n++); } printf("\n"); } } int main() { int n = 4;</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d", n++); } printf("\n"); } } int main() { int n = 4; pattern(n);</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d", n++); } printf("\n"); } } int main() { int n = 4; pattern(n);</stdio.h>	11	1
a) finclude <stdio.h> nt main() { int a = 5, b = 10; int *x, *y; x = &a y = &b *x += a, *y += b; printf("a=%d b=%d\n", *y+a, b); printf("x=%d y=%d\n", *x, a+ *y);</stdio.h>	b) #include <stdio.h> void pattern(int r) { int i, n = 1,j; for (i = 1; i <= r; i++) { for (j = 1; j <= i; j++) { printf("%d", n++); } printf("\n"); } } int main() { int n = 4; pattern(n);</stdio.h>	11	1

c)	3	
#include <stdio.h></stdio.h>		
void countdown(int n) {		
$if (n \le 0) \{$		
<pre>printf("Blastoff!\n");</pre>		
} else {		
printf("%d\n", n);		
countdown(n - 1); // Recursive call with n-1		
}		
}		
int main() {		
int start = 5;		
countdown(start);		l
return 0;		l
}		١
Identify the problems scenarios given below to write a full program for each of the following:		
a) In a severe heat wave in Bangladesh, the government launches a Heat Wave Advisory System to aid citizens in navigating extreme temperatures. Write a C program to provide warnings based on current	[5]	

nperatures. Write a C program to provide warnings based on current temperature readings. Input:

An integer representing the current temperature.

"Baire Agun" if the temperature exceeds 40 degrees. "Sabdhane Jao" if the temperature is between 30 and 40 degrees (inclusive). "Baire Jaoa Jabe" if the temperature is less than 30 degrees,

personal to together to the second		
Sample Input	Sample output	
30	Sabdhane Jao	
41	Baire Agun	

b) In recent heat waves in Bangladesh, authorities have implemented a Temperature Monitoring and

Analysis system. Write a C program to analyze consecutive temperatures over 7 days from monitoring

[5]

[5]

stations. If temperatures exceed 35°C for more than 3 days, print "Heat-wave Burning". Otherwise, print "No more heat waves". Input:

Seven integers representing the temperatures recorded over consecutive 7 days.

Output:

"Heat-wave Burning" or. "No more

heat wave" otherwise.	
Sample Input	Sample output
25 29 31 36 34 37 35	No more heat wave
31 34 37 36 30 39 38	Heat-wave Burning

c) During the COVID-19 pandemic, authorities are closely monitoring the spread of the virus across different regions. Write a program that takes a 2D array representing a grid of regions and their COVID-19 infection rates. The program should identify the highest infection rate and display it.

Input: An integer N ($1 \le N \le 100$) representing the number of rows and columns in the grid. N lines, each containing N integers representing the COVID-19 infection rates in each region. For more questions: https://diuqbank.com | Uploader: Mehrab Hossain Rahi 241-15-419

Output: The highest infection rate.

10	
Sample Input	Sample Output
100 200 150 300 250 180	300
210 190 220	

d) Sarah is intrigued by the idea of transforming strings in unusual ways. She creates a program that replaces all vowels in a given string with a specified character. With this program, Sarah can input any string of characters and specify the character she wants to replace the vowels with. This unique transformation allows Sarah to explore unconventional text manipulation techniques and experiment with creative ways to modify strings in her programming projects.

Write a program that replaces all vowels in a given string with a specified character.

Input: A string of characters. Next line, The character to replace the vowels with.

Output: The modified string with vowels replaced.

	18.20
Sample Input	Sample Output
Sample Input	h*ll* w*rld
hello world	hall, walle
*	

e) In a heat wave, Sarah is exploring different ways to keep her mind engaged while staying indoors. She recalls the concept of palindromes(A palindrome is a sequence of characters that reads the same forwards and backward. For example, "radar" and "madam" are palindromic words, while "hello" and "12345" are not palindromes.) and decides to write a program to check if a given string is a palindrome. With this program, Sarah can challenge herself by entering various strings and testing whether they form palindromes. This activity not only helps Sarah pass the time but also enhances her understanding of programming concepts.

Write a program that checks if a given string is a palindrome.

Input: A string of characters.

Output:

"Palindrome" if the input string is a palindrome.

"Not a palindrome" if the input string is not a palindrome.

Sample Input	Sample Output
radar	Palindrome
hello	Not a palindrome